

# HDMI Chainable Extender over CAT.5e/6

## Model No. HCE-100


The HCE-100 is the high performance, cost-effective HDMI Extender over CAT. 5e/6 up to 100m at the best strengthened competitive price in the market. HCE-100 supports Full HD 1080p video and daisy-chainable with high flexibility for expansion.



### Features:

- Uses easy to install, inexpensive CAT. 5e/6 cables
- Each pair (TX & RX) extends the signals up to 100m (330 feet)
- Supports video high resolution up to 1920x1080, Full HD 1080p
- HDTV compatible (720p, 1080i, 1080p)
- Supports High Definition Audio (HD) Surround Sound
  - Daisy-chainable receiver up to 10 layers
  - Supports RS-232 (Serial)
  - IR (Infrared remote) enabled
- Supports Local HDMI monitoring port
- Each receiver (remote) links cascade-chainable 2 receivers
- Bracket mountable

### Application Diagram




## Connection Diagram


### (1) Single Source Extension



### (2) Single Source Extension and Receivers Cascade Chaining



### (3) Single Source with Multiple Receivers Cascaded



#### Transmitter (TX) – Front View



- ①: Connected to Power Adapter DC 5V/2A
- ②: Power LED (Solid Red when power present)
- ③: Link LED (Solid Green when link present)
- ④: RS-232 control port
- ⑤: HDMI IN, connected to HDMI source

#### Transmitter (TX) – Rear View



- ⑥: HDMI OUT, connected to display
- ⑦: CAT.5e/6 cable connected for data out
- ⑧: IR Blaster Emitter
- ⑨: Reset Button

#### Receiver (RX) – Front View



- ①: CAT.5e/6 cable connected for data in or out
- ②: CAT.5e/6 cable connected for data in or out
- ③: CAT.5e/6 cable connected for data in or out
- ④: Connected to Power Adapter DC 5V/2A
- ⑤: IR Receiver

#### Receiver (RX) – Rear View



- ⑥: Reset Button
- ⑦: Power LED (Solid Red when power present)
- ⑧: Link LED (Solid Green when link present)
- ⑨: RS-232 control port
- ⑩: HDMI OUT, connected to display

## Specifications

		HCE-100TX (Transmitter)	HCE-100RX (Receiver)
Console	HDMI Output	HDMI (Female)	HDMI (Female)
Connectors	RS-232 Control Port	Phone Jack	Phone Jack
PC Connectors	HDMI Input	HDMI (Female)	N/A
Extension Port	RJ-45	Full HD Video / Audio Extension	
RJ-45		1 (Line Out)	3 (Line In or Line Out)
Cascaded-Chainable		N/A	Yes, up to 10 layers
Audio		Supports High Definition Audio (HD) , Surround Sound	
IR		Bi-directional	
LED Indicators	Local	Power	Red LED
		Link	Red Green
	Remote	Power	Red LED
		Link	Red Green
DDC Supported		DDC, DDC2, DDC2B	
Extension Cable Type & Length		CAT.5e / CAT.6 Max. Length: 100m	
Max. Video Resolution		1920x1080@60Hz, Full HD 1080p, 48-bit	
Wide Screen Supported		Yes	
OS Compatibility		OS Independent	
Power Supply		External DC 5V / 2A Power Adapter	
Dimension ( L x W x H )		115 x 91 x 28 mm	
Weight		340g	380g
Housing material		Metal	
Operating Temperature		32 - 122 ° F ( 0 - 50 ° C )	
Humidity		0% - 80% RH	

## Accessories



- A. DC 5V 2A power adaptor
- B. IR cable (optional)
- C. RS-232 cable (optional)